

晶采光電科技股份有限公司 AMPIRE CO., LTD.

SPECIFICATIONS FOR LCD MODULE

CUSTOMER	
CUSTOMER PART NO.	
AMPIRE PART NO.	AM-640480GJTNQW-TA0H
APPROVED BY	
DATE	

□Approved For Specifications □Approved For Specifications & Sample

AMPIRE CO., LTD. Building A., 4F., No.116, Sec. 1, Sintai 5th Rd., Xizhi Dist, New Taipei City 221, Taiwan (R.O.C.) 新北市汐止區新台五路一段 116 號 4 樓(東方科學園區 A 棟) TEL:886-2-26967269, FAX:886-2-26967196 or 26967270

APPROVED BY	CHECKED BY	ORGANIZED BY

RECORD OF REVISION

Date	Lanton
2013/5/16 New Release	Bob

1. INTRODUCTION

This is a color active matrix TFT-LCD that uses amorphous silicon TFT as a switching device . This model is composed of a 5.7inch TFT-LCD panel , a driving circuit and LED backlight system and touch panel. This TFT-LCD has a high resolution (640(R.G.B) X 480) and can display up to 262,144 colors.

1-1. Features

- VGA Resolution
- 6 Bits color driver with LVDS interface
- Wide range operation temperature
- 4 layers PCB for EMI reduction
- •capacitive-type touch panel.

For normal operation, there must be a cover lens of 0.7~4mm thickness to be put on the top of touch panel.

• USB interface for touch control.

2. PHYSICAL SPECIFICATIONS

Item	Specifications	unit
Display resolution(dot)	640RGB (W) x 480(H)	dots
Display area	115.2 (W) x 86.4 (H)	mm
Pixel pitch	0.18 (W) x 0.18 (H)	mm
Color configuration	R.G.B Vertical stripe	
Overall dimension	127.0(W)x98.43(H)x9.538(D)(Typ)	mm
Brightness	425	cd/m ²
Contrast ratio	250 : 1	
Backlight unit	LED	
Display color	262,144	colors
Viewing Direction	12 o'clock	
Display Mode	Normally White	

3. ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN	MAX	UNIT	NOTE
Power Supply Voltage	Vcc	-0.5	5	V	
Signal Input Voltage	DCLK , DE R0~R5 G0~G5 B0~B5	-0.5	Vcc + 0.5	V	
Operation Temperature	Тор	-20	70	°C	
Storage Temperature	Tstg	-30	80	°C	

4. ELECTRICAL CHARACTERISTICS

4-1 TFT LCD Module voltage

ITEM	SYMBOL	MIN	TYP	MAX	UNIT	NOTE
Power Voltage For LCD	V _{CC}	3.0	3.3	3.6	V	
Power Voltage For VLED	V_{DD}		5.0		V	
Logio Input Voltago	VIH	V _{CC} *0.7		V _{CC}	V	
	VIL	0		V _{CC} *0.3	V	
	VIH	3.0		5.0	V	
	VIL	GND		0.3	V	

4-2 TFT LCD current comsumption

ITEM	SYMBOL	MIN	TYP	MAX	UNIT	NOTE
LCD Power Current	lcc	-	106	-	mA	(1)
LED Power Current	I _{LED} (VLED=5V)	-	290	-	mA	

NOTE : (1) Typ : under 64 gray pattern Max : under black pattern





(a) 64 Gray Pattern

(b) Black Pattern

6. INTERFACE

LVDS CN1:

Pin no	Symbol	Function
1	VDD	POWER SUPPLY:3.3V
2	VDD	POWER SUPPLY:3.3V
3	Gnd	Power Ground
4	Gnd	Power Ground
5	IN0-	Transmission Data of Pixels
6	IN0+	Transmission Data of Pixels
7	Gnd	Power Ground
8	IN1-	Transmission Data of Pixels 1
9	IN1+	Transmission Data of Pixels 1
10	Gnd	Power Ground
11	IN2-	Transmission Data of Pixels 2
12	IN2+	Transmission Data of Pixels 2
13	Gnd	Power Ground
14	CLK-	Sampling Clock
15	CLK+	Sampling Clock
16	Gnd	Power Ground
17	VLED	Power Supply for LED Backlight : 5V
18	VLED	Power Supply for LED Backlight : 5V
19	Gnd	Power Ground
20	ADJ	LED backlight adjustment

NOTE :

1. ADJ adjust brightness to control Pin , Pulse duty the bigger the brighter.



3. VSS Pin must ground contact , can not be floating.

7. AC Timing characteristic of the LVDS

7.1 Timing Parameter

Switching Characteristics

over recommended operating conditions (unless otherwise noted)

	PARAMETER	TEST CONDITIONS	MIN	TYP ⁽¹⁾	MAX	UNIT
t _{su}	Setup time, D0–D20 to CLKOUT↓		5			ns
t _h	Data hold time, CLKOUT↓ to D0–D20	$-C_L = \delta pr, See Figure 5$	5			ns
t _(RSKM)	Receiver input skew margin ⁽²⁾ (see Figure 7)	t _c = 15.38 ns (±0.2%), Input clock jitter < 50 ps, ⁽³⁾	550	700		ps
t _d	Delay time, CLKIN [↑] to CLKOUT \downarrow (see Figure 7)	V _{CC} = 3.3 V, t _c = 15.38 ns (±0.2%), T _A = 25°C	3	5	7	ns
t _{en}	Enable time, SHTDN to phase lock	See Figure 7		1		ms
t _{dis}	Disable time, SHTDN to off state	See Figure 8		400		ns
t _t	Transition time, output (10% to 90% t_r or t_f) (data only)	C _L = 8 pF		3		ns
t _t	Transition time, output (10% to 90% t_r or t_f) (clock only)	C _L = 8 pF		1.5		ns
t _w	Pulse duration, output clock			0.50 t _c		ns

All typical values are at V_{CC} = 3.3 V, T_A = 25°C.
The parameter t_(RSKM) is the timing margin available to allocate to the transmitter and interconnection skews and clock jitter. The value of this parameter at clock periods other than 15.38 ns can be calculated from t_{RSKM} = tc/14 - 550 ps.
Input clock jitter] is the magnitude of the change in input clock period.

PARAMETER MEASUREMENT INFORMATION (continued)



Figure 5. Setup and Hold Time Waveforms

PARAMETER MEASUREMENT INFORMATION (continued)



Figure 8. Disable Time Waveforms

PARAMETER	Symbol	Min.	Тур.	Max	Unit
CLK frequency	Fсрн		25.175		MHz
CLK period	Тсрн	-	39.7	-	ns
CLK pulse duty	Тсwн	40	50	60	%
HS period	Тн	-	800	-	Тсрн
HS pulse width	Тwн	5	30	-	Тсрн
HS-first horizontal data time	Tнs	112	144	175	Тсрн
DEN pulse width	Tep	-	640	-	Тсрн
VS pulse width	Twv	1	3	5	Тн
VS-DEN time	Tstv	-	35	-	Тн
VS period	Τv	-	525	-	Тн

7.2 Recommended Input Timing of LVDS transmitter

Note: When SYNC mode is used, 1st data start from 144th CLK after HS falling (when STHD[5:0]=00000)

PARAMETER	Symbol	Min.	Тур.	Max	Unit
OEV pulse width	TOEV		100	-	Тсрн
CKV pulse width	Тску	-	96	-	Тсрн
HS-CKV time	T ₁	-	52	-	Тсрн
HS-OEV time	T ₂	-	8	-	Тсрн
HS-POL time	Тз	-	72	-	Тсрн
STV setup time	Tsuv	-	46	-	Тсрн
STV pulse width	Twstv	-	1	-	Тн







Parallel RGB SYNC Mode Horizontal Data Format



Parallel RGB DE Mode Horizontal Data Format

8. Projected capacitive-type touch panel

For normal operation, there must be a cover lens of 0.7~4mm thickness to be put on the top of touch panel.

Pin No	Symbol	Function
1	VCC	Power Supply for TP controller
2	D+	Data+
3	D+	Data+
4	GND	Ground
5	D-	Data-
6	D-	Data-
7	NC	
8	NC	

Touch Control for USB interface

ITEM	SYMBOL	MIN	TYP	MAX	UNIT
Power Voltage For TP controller	VCC		5.0		V

9. OPTICAL CHARACTERISTICS

Item		Symbol	Condition	Min.	Тур.	Max.	Unit	Note	
Contrast ratio		CR	Point - 5 Θ=⊕=0°	200	250			(1)(2)(3)	
Luminance		Lw		340	425	-	cd/m ²	(1)(3)	
Luminance Uniformity		ΔL		70	75	-	%	(1)(3)	
Response Time (White – Black)		T _r +T _f			50		ms	(1)(3)(5)	
Viewing Angle	Ve	ertical Θ		CR≧10	80	100	-	Dec	(1)(2)(4)
	Hor	izontal	Φ	Point – 5	120	140	-	Deg.	(1)(2)(4)
Color chromaticity		Red	Rx	Point - 5 Θ=⊕=0°	0.566	0.616	0.666		(1)(3)
			Ry		0.302	0.352	0.402		
		Green	Gx		0.308	0.358	0.408		
			Gy		0.518	0.568	0.618		
		Blue	Bx		0.096	0.146	0.196		
			Ву		0.086	0.136	0.186		
		White	Wx		0.296	0.346	0.396		
			Wy		0.328	0.378	0.428		
LED life time			Ta = 25 ℃		20K		hour	(1)(6)	

NOTE :

(1) Measure conditions : 25°C ±2°C , 60±10%RH under 10Lux , in the dark room by BM-7TOPCON) ,viewing 2° , VCC=3.3V , VDD=3.3V



(2) Definition of Contrast Ratio :

Contrast Ratio (CR) = (White) Luminance of ON ÷ (Black) Luminance of OFF

 (3) Definition of Luminance : Definition of Luminance Uniformity Measure white luminance on the point 5 as figure9-1 Measure white luminance on the point 1 ~ 9 as figure9-1
△L = [L(MIN) / L(MAX)] X 100%



Fig9-1 Measuring point

(4) Definition of Viewing Angle(Θ, Φ), refer to Fig9-2 as below :



Fig9-2 Definition of Viewing Angle

(5) Definition of Response Time.(White – Black)



- Fig9-3 Definition of Response Time(White-Black)
- (6) End of Life shall be determined by the time when any of the following is satisfied under continuous lighting at 25° C.
 - Intensity drops to 50% of the Initial Value (Min. Luminance)
 - Based on LED
 - It is an estimative value

10. RELIABILITY TEST CONDITIONS

ITEM	CONDITIONS
HIGH TEMPERATURE OPERATION	70℃,240Hrs
HIGH TEMPERATURE AND HIGH HUMIDITY OPERATION	$60^\circ\!\!\mathbb{C}$, 90%RH , 240Hrs
HIGH TEMPERATURE STORAGE	80℃,240Hrs
LOW TEMPERATURE OPERATION	-20℃,240Hrs
LOW TEMPERATURE STORAGE	-30℃,240Hrs
THERMAL SHOCK	-30°C (0.5Hr) ~80°C (0.5Hr) 200Cycle

11. General Precautions

11-1 Safety

Liquid crystal is poisonous. Do not put it your month. If liquid crystal touches your skin or clothes, wash it off immediately by using soap and water.

11-2 Handling

1. The LCD panel is plate glass. Do not subject the panel to mechanical shock or to excessive force on its surface.

2. The polarizer attached to the display is easily damaged. Please handle it carefully to avoid scratch or other damages.

3. To avoid contamination on the display surface, do not touch the module surface with bare hands.

4. Keep a space so that the LCD panels do not touch other components.

5. Put cover board such as acrylic board on the surface of LCD panel to protect panel from damages.

6. Transparent electrodes may be disconnected if you use the LCD panel under environmental conditions where the condensation of dew occurs.

7. Do not leave module in direct sunlight to avoid malfunction of the ICs.

11-3 Static Electricity

1. Be sure to ground module before turning on power or operation module.

2. Do not apply voltage which exceeds the absolute maximum rating value.

11-4 Storage

1. Store the module in a dark room where must keep at +25±10 $^\circ\!C$ and 65%RH or less.

2. Do not store the module in surroundings containing organic solvent or corrosive gas.

3. Store the module in an anti-electrostatic container or bag.

11-5 Cleaning

1. Do not wipe the polarizer with dry cloth. It might cause scratch.

2. Only use a soft sloth with IPA to wipe the polarizer, other chemicals might permanent damage to the polarizer.

11-6 Others

1. AMIPRE will provide one year warrantee for all products and three months warrantee for all repairing products.

2. The residual image may exist if the same display pattern is shown for hours. This residual image, however, disappears when another display pattern is shown or the drive is interrupted and left for a while. But this is not a problem on reliability.

11. OUTLINE DIMENSION



Date: 2013/5/16



Date: 2013/5/16