


#### ■ Features

- Landscape, 5.0 inch QVGA resolution.
- High brightness & high color purity slim LCD module using long-life LED.
- TC, Power-circuit on panel.



#### ■ Specifications

RoHS compliant

Items	Specifications	Units	Notes
Display Size	12.6 (5.0)	cm (inch)	
Display Format	320 X RGB X 240 Stripe	--	
Dot Pitch	105.00(H) X 315.00(V)	$\mu$ m	
Outline Dimensions	108.3 (H) X 87.55 (V) X 3.0 (D)	mm	
Weight	60.5	g	
Number of Colors	262,144/16,777,216	--	*1
Brightness	500 (TYP)	cd/m <sup>2</sup>	
Viewing Angle(U/D/L/R)	20/50/35/35	deg.	CR $\geq$ 10
Input Signal Type	Digital RGB signal (each 6/8 bit parallel)	--	*1
Power Supplies	3.0 (without B/L)	V	
Operating Temperature	-20 ~ +70	°C	
Storage Temperature	-30 ~ +80	°C	
Backlight	LED Backlight	--	
Remarks	*1 Each 6/8 bit can be selected by change of mode.		

※ Specifications are subject to change without notice.

2010.07.01

## ORTUS TECHNOLOGY CO., LTD.

### Sales HQ, Overseas Sales Dept.

2951-5 Ishikawa-machi, Hachioji City, Tokyo 192-8556, Japan  
 TEL +81-42-639-5121 FAX +81-42-639-5034

<http://www.ortustech.co.jp>

All Rights Reserved, Copyright (C) ORTUS TECHNOLOGY CO., LTD.

Contact