

# SPECIFICATION FOR APPROVAL

( ● ) Preliminary Specification

(   ) Final Specification

|       |                     |
|-------|---------------------|
| Title | 47.0" WUXGA TFT LCD |
|-------|---------------------|

|       |         |
|-------|---------|
| BUYER | General |
| MODEL |         |

|          |                      |
|----------|----------------------|
| SUPPLIER | LG.Display Co., Ltd. |
| *MODEL   | LD470WUN             |
| SUFFIX   | SCA1                 |

\*When you obtain standard approval,  
please use the above model name without suffix

| APPROVED BY | SIGNATURE | DATE |
|-------------|-----------|------|
| /           |           |      |
| /           |           |      |
| /           |           |      |

Please return 1 copy for your confirmation with  
your signature and comments.

| APPROVED BY                 | SIGNATURE | DATE |
|-----------------------------|-----------|------|
| K. S. Nah / Team Leader     |           |      |
| REVIEWED BY                 |           |      |
| B. Y. Park / Project Leader |           |      |
| PREPARED BY                 |           |      |
| J. H.KIM / Engineer         |           |      |

**PD Products Development Dept.**  
**LG. Display LCD Co., Ltd**

## Product Specification

**CONTENTS**


| Number | ITEM                                     | Page |
|--------|--|------|
|        | COVER                                    | 1    |
|        | CONTENTS                                 | 2    |
|        | RECORD OF REVISIONS                      | 3    |
| 1      | GENERAL DESCRIPTION                      | 4    |
| 2      | ABSOLUTE MAXIMUM RATINGS                 | 5    |
| 3      | ELECTRICAL SPECIFICATIONS                | 6    |
| 3-1    | ELECTRICAL CHARACTERISTICS               | 6    |
| 3-2    | INTERFACE CONNECTIONS                    | 8    |
| 3-3    | SIGNAL TIMING SPECIFICATIONS             | 10   |
| 3-4    | LVDS SIGNAL SPECIFICATIONS               | 11   |
| 3-5    | COLOR DATA REFERENCE                     | 14   |
| 3-6    | POWER SEQUENCE                           | 15   |
| 4      | OPTICAL SPECIFICATIONS                   | 17   |
| 5      | MECHANICAL CHARACTERISTICS               | 21   |
| 6      | RELIABILITY                              | 24   |
| 7      | INTERNATIONAL STANDARDS                  | 25   |
| 7-1    | SAFETY                                   | 25   |
| 7-2    | EMC                                      | 25   |
| 7-3    | Environment                              | 25   |
| 8      | PACKING                                  | 26   |
| 8-1    | INFORMATION OF LCM LABEL                 | 26   |
| 8-2    | PACKING FORM                             | 26   |
| 9      | PRECAUTIONS                              | 27   |
| 9-1    | MOUNTING PRECAUTIONS                     | 27   |
| 9-2    | OPERATING PRECAUTIONS                    | 27   |
| 9-3    | ELECTROSTATIC DISCHARGE CONTROL          | 28   |
| 9-4    | PRECAUTIONS FOR STRONG LIGHT EXPOSURE    | 28   |
| 9-5    | STORAGE                                  | 28   |
| 9-6    | HANDLING PRECAUTIONS FOR PROTECTION FILM | 28   |

[illegible]

## Product Specification

## 1. General Description

The LD470WUN is a Color Active Matrix Liquid Crystal Display with an integral External Electrode Fluorescent Lamp(EEFL) backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive display type which is operating in the normally black mode. It has a 46.96 inch diagonally measured active display area with WUXGA resolution (1080 vertical by 1920 horizontal pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arrayed in vertical stripes. Gray scale or the luminance of the sub-pixel color is determined with a 10-bit gray scale signal for each dot. Therefore, it can present a palette of more than 1.06Billion (true) colors. It has been designed to apply the 10-bit 2-port LVDS interface. It is intended to support LCD TV, PCTV where high brightness, super wide viewing angle, high color gamut, high color depth and fast response time are important.



## General Features

|                       |  |
|-----------------------|--|
| Active Screen Size    | 46.96 inches(1192.87mm) diagonal   |
| Outline Dimension     | 1096.0(H) x 640.0 (V) x 53.0 mm(D) (Typ.)                                |
| Pixel Pitch           | 0.5415 mm x 0.5415 mm  |
| Pixel Format          | 1920 horiz. by 1080 vert. Pixels, RGB stripe arrangement                 |
| Color Depth           | 10bit(D) , 1.06Billion colors  |
| Luminance, White      | 500 cd/m <sup>2</sup> (Center 1point ,Typ.)                              |
| Viewing Angle (CR>10) | Viewing angle free ( R/L 178 (Min.), U/D 178 (Min.))                     |
| Power Consumption     | Total 201.7W (Typ.) (Logic=6.7W, Inverter=195W )                         |
| Weight                | 12.5Kg (Typ.)  |
| Display Mode          | Transmissive mode, Normally black  |
| Surface Treatment     | Hard coating(3H), Anti-glare treatment of the front polarizer (Haze 10%) |

## Product Specification

## 2. Absolute Maximum Ratings

The following items are maximum values which, if exceeded, may cause faulty operation or damage to the LCD module.


**Table 1. ABSOLUTE MAXIMUM RATINGS**

| Parameter                  |                    | Symbol              | Value |       | Unit            | Remark       |
|----------------------------|--------------------|---------------------|-------|-------|-----------------|--------------|
|                            |                    |                     | Min   | Max   |                 |              |
| Power Input Voltage        | LCM                | V <sub>LCD</sub>    | -0.3  | +14.0 | V <sub>DC</sub> | at 25 ± 2 °C |
|                            | Backlight inverter | V <sub>BL</sub>     | -0.3  | +27.0 | V <sub>DC</sub> |              |
| ON/OFF Control Voltage     |                    | V <sub>ON/OFF</sub> | -0.3  | +5.5  | V <sub>DC</sub> |              |
| Brightness Control Voltage |                    | V <sub>BR</sub>     | 0     | +5.0  | V <sub>DC</sub> |              |
| Operating Temperature      |                    | T <sub>OP</sub>     | 0     | +50   | °C              | Note 1,2     |
| Storage Temperature        |                    | T <sub>ST</sub>     | -20   | +60   | °C              |              |
| Operating Ambient Humidity |                    | H <sub>OP</sub>     | 10    | 90    | %RH             |              |
| Storage Humidity           |                    | H <sub>ST</sub>     | 10    | 90    | %RH             |              |

Notes 1. Ambient temperature condition (T<sub>a</sub> = 25 ± 2 °C )

2. Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be Max 39°C, and no condensation of water.



## Product Specification

### 3. Electrical Specifications

#### 3-1. Electrical Characteristics

It requires two power inputs. One is employed to power for the LCD circuit. The other is used for the EEFL backlight and inverter circuit.

**Table 2. ELECTRICAL CHARACTERISTICS**

| Parameter           | Symbol            | Value |      |      | Unit            | Note |
|---------------------|-------------------|-------|------|------|-----------------|------|
|                     |                   | Min   | Typ  | Max  |                 |      |
| Circuit :           |                   |       |      |      |                 |      |
| Power Input Voltage | V <sub>LCD</sub>  | 10.8  | 12.0 | 13.2 | V <sub>DC</sub> |      |
| Power Input Current | I <sub>LCD</sub>  | -     | 560  | 730  | mA              | 1    |
|                     |                   | -     | 870  | 1150 | mA              | 2    |
| Power Consumption   | P <sub>LCD</sub>  |       | 6.72 | 8.76 | Watt            | 1    |
| Rush current        | I <sub>RUSH</sub> | -     | -    | 5.0  | A               | 3    |


Note 1. The specified current and power consumption are under the  $V_{LCD}=12.0V$ ,  $T_a=25 \pm 2^{\circ}C$ ,  $f_v=60Hz$  condition whereas mosaic pattern(8 x 6) is displayed and  $f_v$  is the frame frequency.

2. The current is specified at the maximum current pattern.

3. The duration of rush current is about 2ms and rising time of power input is 0.5ms (min.).

White : 1023 Gray

Black : 0 Gray



**Mosaic Pattern(8 x 6)**

## Product Specification

Table 3. ELECTRICAL CHARACTERISTICS (Continue)

| Parameter                                |                                     |     | Symbol               | Values |        |      | Unit | Note  |
|--|-------------------------------------|-----|----------------------|--------|--------|------|------|---|
|  |                                     |     |                      | Min    | Typ    | Max  |      |   |
| Inverter :                               |                                     |     |                      |        |        |      |      |   |
| Power Supply Input Voltage               |                                     |     | VBL                  | 22.8   | 24.0   | 25.2 | VDC  | 1   |
| Power Supply Input Current               | After Aging                         |     | IBL_A                | -      | 8.2    | 9.0  | A    | 1   |
|  | Before Aging                        |     | IBL_B                | -      | 9.0    | 9.9  | A    | 2   |
| Power Supply Input Current (In-Rush)     |                                     |     | IRUSH                | -      | -      | 15   | A    | VBL = 22.8V<br>EXTV <sub>BR-B</sub> = 100%<br>6 |
| Power Consumption                        |                                     |     | PBL                  | -      | 195    | 214  | W    | 1   |
| Input Voltage for Control System Signals | On/Off                              | On  | VON                  | 2.5    | -      | 5.0  | VDC  |   |
|  |                                     | Off | VOFF                 | -0.3   | 0.0    | 0.8  | VDC  |   |
|  | Brightness Adjust                   |     | EXTV <sub>BR-B</sub> | 25     | -      | 100  | %    | On Duty<br>7                                    |
|  | PWM Frequency for NTSC & PAL        |     | PAL                  |        | 100    |      | Hz   | 5   |
|  |                                     |     | NTSC                 |        | 120    |      | Hz   | 5   |
|  | Pulse Duty Level (PWM) (Burst mode) |     | High Level           | 2.5    | -      | 5.0  | VDC  | High: Lamp on<br>Low : Lamp off                 |
|  |                                     |     | Low Level            | 0.0    | -      | 0.8  | VDC  |   |
| Lamp:                                    |                                     |     |                      |        |        |      |      |   |
| Discharge Stabilization Time             |                                     |     | Ts                   |        |        | 3    | min  | 3   |
| Life Time                                |                                     |     |                      | 50,000 | 60,000 |      | Hrs  | 4   |

- Note 1. Electrical characteristics are determined after the unit has been 'ON' and stable for approximately 120 minutes at  $25 \pm 2^\circ\text{C}$ . The specified current and power consumption are under the typical supply Input voltage 24V and V<sub>BR</sub> (EXTV<sub>BR-B</sub> : 100%), it is total power consumption.
2. Electrical characteristics are determined within 30 minutes at  $25 \pm 2^\circ\text{C}$ .  
The specified currents are under the typical supply Input voltage 24V.
3. The brightness of the lamp after lighted for 5minutes is defined as 100%.  
TS is the time required for the brightness of the center of the lamp to be not less than 95% at typical current.  
The screen of LCD module may be partially dark by the time the brightness of lamp is stable after turn on.
4. Specified Values are for a single lamp which is aligned horizontally.  
The life time is determined as the time which luminance of the lamp is 50% compared to that of initial value at the typical lamp current (EXTV<sub>BR-B</sub> : 100%), on condition of continuous operating at  $25 \pm 2^\circ\text{C}$
5. LGD recommend that the PWM freq. is synchronized with Two times harmonic of Vsync signal of system.
6. The duration of rush current is about 10ms.
7. EXTV<sub>BR-B</sub> is based on input PWM duty of the inverter.

## Product Specification

### 3-2. Interface Connections

This LCD module employs two kinds of interface connection, 51-pin connector is used for the module electronics and 14-pin connector is used for the integral backlight system.

#### 3-2-1. LCD Module

- LCD Connector : FI-R51S-HF(manufactured by JAE) or KN25-51P-0.5SH(manufactured by Hirose)  
(CN1) Refer to below table
- Mating Connector : FI-R51HL(JAE) or compatible

**Table 4. MODULE CONNECTOR(CN1) PIN CONFIGURATION**

| No | Symbol      | Description                         | No | Symbol     | Description                          |
|----|-------------|-------------------------------------|----|------------|--------------------------------------|
| 1  | NC          | No Connection                       | 27 | Bit Select | 'H' or NC= 10bit(D) , 'L' = 8bit     |
| 2  | NC          | No Connection                       | 28 | R2AN       | SECOND LVDS Receiver Signal (A-)     |
| 3  | NC          | No Connection                       | 29 | R2AP       | SECOND LVDS Receiver Signal (A+)     |
| 4  | NC          | No Connection (Reserved for LGD)    | 30 | R2BN       | SECOND LVDS Receiver Signal (B-)     |
| 5  | NC          | No Connection (Reserved for LGD)    | 31 | R2BP       | SECOND LVDS Receiver Signal (B+)     |
| 6  | NC          | No Connection (Reserved for LGD)    | 32 | R2CN       | SECOND LVDS Receiver Signal (C-)     |
| 7  | LVDS Select | 'H' = JEIDA , 'L' or NC = VESA      | 33 | R2CP       | SECOND LVDS Receiver Signal (C+)     |
| 8  | EXTVBR-B    | External VBR (From System)          | 34 | GND        | Ground                               |
| 9  | VBR-B out   | OPC output (From LCM)               | 35 | R2CLKN     | SECOND LVDS Receiver Clock Signal(-) |
| 10 | OPC Enable  | 'H' = Enable , 'L' or NC = Disable  | 36 | R2CLKP     | SECOND LVDS Receiver Clock Signal(+) |
| 11 | GND         | Ground                              | 37 | GND        | Ground                               |
| 12 | R1AN        | FIRST LVDS Receiver Signal (A-)     | 38 | R2DN       | SECOND LVDS Receiver Signal (D-)     |
| 13 | R1AP        | FIRST LVDS Receiver Signal (A+)     | 39 | R2DP       | SECOND LVDS Receiver Signal (D+)     |
| 14 | R1BN        | FIRST LVDS Receiver Signal (B-)     | 40 | R2EN       | SECOND LVDS Receiver Signal (E-)     |
| 15 | R1BP        | FIRST LVDS Receiver Signal (B+)     | 41 | R2EP       | SECOND LVDS Receiver Signal (E+)     |
| 16 | R1CN        | FIRST LVDS Receiver Signal (C-)     | 42 | NC         | No Connection                        |
| 17 | R1CP        | FIRST LVDS Receiver Signal (C+)     | 43 | NC         | No Connection                        |
| 18 | GND         | Ground                              | 44 | GND        | Ground                               |
| 19 | R1CLKN      | FIRST LVDS Receiver Clock Signal(-) | 45 | GND        | Ground                               |
| 20 | R1CLKP      | FIRST LVDS Receiver Clock Signal(+) | 46 | GND        | Ground                               |
| 21 | GND         | Ground                              | 47 | NC         | No connection                        |
| 22 | R1DN        | FIRST LVDS Receiver Signal (D-)     | 48 | VLCD       | Power Supply +12.0V                  |
| 23 | R1DP        | FIRST LVDS Receiver Signal (D+)     | 49 | VLCD       | Power Supply +12.0V                  |
| 24 | R1EN        | FIRST LVDS Receiver Signal (E-)     | 50 | VLCD       | Power Supply +12.0V                  |
| 25 | R1EP        | FIRST LVDS Receiver Signal (E+)     | 51 | VLCD       | Power Supply +12.0V                  |
| 26 | NC          | No Connection                       | -  | -          | -                                    |

- Note**
1. All GND(ground) pins should be connected together to the LCD module's metal frame.
  2. All VLCD (power input) pins should be connected together.
  3. All Input levels of LVDS signals are based on the **EIA 644** Standard.
  4. Specific pins(pin No. **#2~#6**) are used for internal data process of the LCD module.  
These pins should be no connection.
  5. Specific pins(pin No. **# 8~#10**) are used for OPC function of the LCD module.  
If not used, these pins are no connection. (Please see the **Appendix III-4** for more information.)
  6. LVDS pin (pin No. **#24,25,40,41**) are used for 10Bit(D) of the LCD module.  
If used for 8Bit(R), these pins are no connection.
  7. Specific pin No. **#44** is used for "No signal detection" of system signal interface.  
It should be GND for NSB(No Signal Black) during the system interface signal is not.  
If this pin is "H", LCD Module displays AGP(Auto Generation Pattern).



## Product Specification

## 3-2-2. Backlight Module

## [ Master ]


- Inverter Connector : 20022WR-14B1(Yeonho)  
or Equivalent
- Mating Connector : 20022HS-14 or Equivalent

Table 5. INVERTER CONNECTOR PIN CONFIGURATION

| Pin No | Symbol   | Description              | Master    | Note |
|--------|----------|--------------------------|-----------|------|
| 1      | VBL      | Power Supply +24.0V      | VBL       |      |
| 2      | VBL      | Power Supply +24.0V      | VBL       |      |
| 3      | VBL      | Power Supply +24.0V      | VBL       |      |
| 4      | VBL      | Power Supply +24.0V      | VBL       |      |
| 5      | VBL      | Power Supply +24.0V      | VBL       |      |
| 6      | GND      | Backlight Ground         | GND       | 1    |
| 7      | GND      | Backlight Ground         | GND       |      |
| 8      | GND      | Backlight Ground         | GND       |      |
| 9      | GND      | Backlight Ground         | GND       |      |
| 10     | GND      | Backlight Ground         | GND       |      |
| 11     | NC       | No Connection            | NC        | 2    |
| 12     | VON/OFF  | Backlight ON/OFF control | VON/OFF   |      |
| 13     | EXTVBR-B | External PWM             | EXT VBR-B |      |
| 14     | Status   | Lamp Status              | Status    | 3    |

- Note
1. GND should be connected to the LCD module's metal frame.
  2. Normal : Low (under 0.7V) / Abnormal : High (upper 3.0V)  
Please see Appendix IV-1 for more information.
  3. Each impedance of pin #12,#13 is over **50[KΩ]**, **50[KΩ]**,

## ◆ Rear view of LCM



## Product Specification

**3-3. Signal Timing Specifications**

Table 6 shows the signal timing required at the input of the LVDS transmitter. All of the interface signal timings should be satisfied with the following specification for normal operation.

**Table 6-1. TIMING TABLE for NTSC (DE Only Mode)**

| ITEM       |                | Symbol           | Min  | Typ   | Max  | Unit            | Note    |
|------------|----------------|------------------|------|-------|------|-----------------|---------|
| Horizontal | Display Period | t <sub>HV</sub>  | -    | 960   | -    | tclk            |         |
|            | Blank          | t <sub>HB</sub>  | 100  | 140   | 240  | tclk            |         |
|            | Total          | t <sub>HP</sub>  | 1060 | 1100  | 1200 | tclk            | 2200/2  |
| Vertical   | Display Period | t <sub>VV</sub>  | -    | 1080  | -    | t <sub>HP</sub> |         |
|            | Blank          | t <sub>VB</sub>  | 11   | 45    | 69   | t <sub>HP</sub> |         |
|            | Total          | t <sub>VP</sub>  | 1091 | 1125  | 1149 | t <sub>HP</sub> |         |
| Frequency  | DCLK           | f <sub>CLK</sub> | 70   | 74.25 | 77   | MHz             | 148.5/2 |
|            | Horizontal     | f <sub>H</sub>   | 65   | 67.5  | 70   | KHz             |         |
|            | Vertical       | f <sub>V</sub>   | 57   | 60    | 63   | Hz              |         |

**Table 6-2. TIMING TABLE for PAL (DE Only Mode)**


| ITEM       |                | Symbol           | Min  | Typ   | Max  | Unit            | Note    |
|------------|----------------|------------------|------|-------|------|-----------------|---------|
| Horizontal | Display Period | t <sub>HV</sub>  | -    | 960   | -    | tclk            |         |
|            | Blank          | t <sub>HB</sub>  | 100  | 140   | 240  | tclk            |         |
|            | Total          | t <sub>HP</sub>  | 1060 | 1100  | 1200 | tclk            | 2200/2  |
| Vertical   | Display Period | t <sub>VV</sub>  | -    | 1080  | -    | t <sub>HP</sub> |         |
|            | Blank          | t <sub>VB</sub>  | 228  | 270   | 300  | t <sub>HP</sub> |         |
|            | Total          | t <sub>VP</sub>  | 1308 | 1350  | 1380 | t <sub>HP</sub> |         |
| Frequency  | DCLK           | f <sub>CLK</sub> | 70   | 74.25 | 77   | MHz             | 148.5/2 |
|            | Horizontal     | f <sub>H</sub>   | 65   | 67.5  | 70   | KHz             |         |
|            | Vertical       | f <sub>V</sub>   | 47   | 50    | 53   | Hz              |         |

**Note** The Input of HSYNC & VSYNC signal does not have an effect on normal operation(DE Only Mode). The performance of the electro-optical characteristics may be influenced by variance of the vertical refresh rate.

## Product Specification

## 3-4. LVDS Signal Specification


## 3-4-1. LVDS Input Signal Timing Diagram



## Product Specification


## 3-4-2. LVDS Input Signal Characteristics

## 1) DC Specification



| Description                   | Symbol          | Min | Max | Unit | Note |
|-------------------------------|-----------------|-----|-----|------|------|
| LVDS Common mode Voltage      | $V_{CM}$        | 1.0 | 1.5 | V    | -    |
| LVDS Input Voltage Range      | $V_{IN}$        | 0.7 | 1.8 | V    | -    |
| Change in common mode Voltage | $\Delta V_{CM}$ |     | 250 | mV   | -    |

## 2) AC Specification




| Description                                   |                | Symbol               | Min  | Max                                 | Unit             | Note |
|---|----------------|----------------------|------|-------------------------------------|------------------|------|
| LVDS Differential Voltage                     | High Threshold | V <sub>TH</sub>      | 100  | 300                                 | mV               | 3    |
|   | Low Threshold  | V <sub>TL</sub>      | -300 | -100                                | mV               |      |
| LVDS Clock to Data Skew Margin                |                | t <sub>SKEW</sub>    |      | ( <b>0.25</b> *T <sub>clk</sub> )/7 | ps               | -    |
| LVDS Clock/DATA Rising/Falling time           |                | t <sub>RF</sub>      | 260  | (0.3*T <sub>clk</sub> )/7           | ps               | 2    |
| Effective time of LVDS                        |                | t <sub>eff</sub>     | ±360 |                                     | ps               | -    |
| LVDS Clock to Clock Skew Margin (Even to Odd) |                | t <sub>SKEW_EO</sub> |      | 1/7* T <sub>clk</sub>               | T <sub>clk</sub> | -    |

Note 1. All Input levels of LVDS signals are based on the EIA 644 Standard.

2. If  $t_{RF}$  isn't enough,  $t_{eff}$  should meet the range.

3. LVDS Differential Voltage is defined within  $t_{eff}$

## Product Specification



## Product Specification

## 3-5. Color Data Reference

The brightness of each primary color(red,green,blue) is based on the 10bit gray scale data input for the color. The higher binary input, the brighter the color. Table 7 provides a reference for color versus data input.

Table 7. COLOR DATA REFERENCE

| Color       |              | Input Color Data |    |    |    |    |     |    |    |    |    |       |    |    |    |    |     |    |    |    |    |      |    |    |    |    |     |    |    |    |    |  |  |
|-------------|--------------|------------------|----|----|----|----|-----|----|----|----|----|-------|----|----|----|----|-----|----|----|----|----|------|----|----|----|----|-----|----|----|----|----|--|--|
|             |              | RED              |    |    |    |    |     |    |    |    |    | GREEN |    |    |    |    |     |    |    |    |    | BLUE |    |    |    |    |     |    |    |    |    |  |  |
|             |              | MSB              |    |    |    |    | LSB |    |    |    |    | MSB   |    |    |    |    | LSB |    |    |    |    | MSB  |    |    |    |    | LSB |    |    |    |    |  |  |
|             |              | R9               | R8 | R7 | R6 | R5 | R4  | R3 | R2 | R1 | R0 | G9    | G8 | G7 | G6 | G5 | G4  | G3 | G2 | G1 | G0 | B9   | B8 | B7 | B6 | B5 | B4  | B3 | B2 | B1 | B0 |  |  |
| Basic Color | Black        | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | Red (1023)   | 1                | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | Green (1023) | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | Blue (1023)  | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  |  |  |
|             | Cyan         | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 1    | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  |  |  |
|             | Magenta      | 1                | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  |  |  |
|             | Yellow       | 1                | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 1     | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | White        | 1                | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 1     | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 1    | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  |  |  |
| RED         | RED (0000)   | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | RED (0001)   | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | ...          | ...              |    |    |    |    |     |    |    |    |    | ...   |    |    |    |    |     |    |    |    |    | ...  |    |    |    |    |     |    |    |    |    |  |  |
|             | RED (1022)   | 1                | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | RED (1023)   | 1                | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
| GREEN       | GREEN (0000) | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | GREEN (0001) | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | ...          | ...              |    |    |    |    |     |    |    |    |    | ...   |    |    |    |    |     |    |    |    |    | ...  |    |    |    |    |     |    |    |    |    |  |  |
|             | GREEN (1022) | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | GREEN (1023) | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1     | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
| BLUE        | BLUE (0000)  | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  |  |  |
|             | BLUE (0001)  | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0    | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 1  |  |  |
|             | ...          | ...              |    |    |    |    |     |    |    |    |    | ...   |    |    |    |    |     |    |    |    |    | ...  |    |    |    |    |     |    |    |    |    |  |  |
|             | BLUE (1022)  | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 0  | 0  |  |  |
|             | BLUE (1023)  | 0                | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 0     | 0  | 0  | 0  | 0  | 0   | 0  | 0  | 0  | 0  | 1    | 1  | 1  | 1  | 1  | 1   | 1  | 1  | 1  | 1  |  |  |

## Product Specification

## 3-6. Power Sequence

## 3-6-1. LCD Driving circuit




Table 8. POWER SEQUENCE


| Parameter | Value |     |     | Unit | Notes |
|-----------|-------|-----|-----|------|-------|
|           | Min   | Typ | Max |      |       |
| T1        | 0.5   | -   | 20  | ms   |       |
| T2        | 0     | -   | -   | ms   | 4     |
| T3        | 200   | -   | -   | ms   | 3     |
| T4        | 200   | -   | -   | ms   | 3     |
| T5        | 1.0   | -   | -   | s    | 5     |
| T6        | -     | -   | T2  | ms   | 4     |
| T7        | 0.5   | -   | -   | S    |       |
| T8        | 100   | -   | -   | ms   | 6     |

- Note : 1. Please avoid floating state of interface signal at invalid period.  
 2. When the power supply for LCD ( $V_{LCD}$ ) is off, be sure to pull down the valid and invalid data to 0V.  
 3. The T3 / T4 is recommended value, the case when failed to meet a minimum specification, abnormal display would be shown. There is no reliability problem.  
 4. If the on time of signals (Interface signal and user control signals) precedes the on time of Power ( $V_{LCD}$ ), it will be happened abnormal display. When T6 is NC status, T6 doesn't need to be measured.  
 5. T5 should be measured after the Module has been fully discharged between power off and on period.  
 6. It is recommendation specification that T8 has to be 100ms as a minimum value.

## Product Specification

## 3-6-2. Sequence for Inverter

## Power Supply For Inverter



## 3-6-3. Dip condition for Inverter




Table 9. Power Sequence for Inverter

| Parameter | Values |     |     | Units | Note                     |
|-----------|--------|-----|-----|-------|--------------------------|
|           | Min    | Typ | Max |       |                          |
| T1        | 20     | -   | -   | ms    | 1                        |
| T2        | 500    | -   | -   | ms    |                          |
| T4        | 0      | -   | -   | ms    | 2                        |
| T5        | 10     | -   | -   | ms    |                          |
| T6        | -      | -   | 10  | ms    | $V_{BL}(Typ) \times 0.8$ |
| T7        | 1000   | -   | -   | ms    | 3                        |

Notes : 1. T1 describes rising time of 0V to 24V and this parameter does not applied at restarting time.

2. T4(max) is less than T2.

3. It is the recommendation to input Max Duty to Inverter\*\* for EXTVBR-B during T7 period.

\*\*When OPC Function is applied, the Max Duty is input to T-Con.

\* The recommendation of VON/OFF rising time is under 10ms.



## Product Specification

#### 4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable in a dark environment at  $25\pm2^{\circ}\text{C}$ . The values are specified at an approximate distance 50cm from the LCD surface at a viewing angle of  $\Phi$  and  $\theta$  equal to  $0^{\circ}$ .

It is presented additional information concerning the measurement equipment and method in FIG. 1.




FIG. 1 Optical Characteristic Measurement Equipment and Method

$T_a = 25\pm2^{\circ}\text{C}$ ,  $V_{\text{LCD}} = 12.0\text{V}$ ,  $f_v = 60\text{Hz}$ ,  $D_{\text{clk}} = 74.25\text{MHz}$ ,  
EXTV<sub>BR-B</sub> = 100%

Table 10. OPTICAL CHARACTERISTICS

EXPER B-100%

| Parameter                      |                       | Symbol              |    | Value        |        |              | Unit              | Note |
|--------------------------------|-----------------------|---------------------|----|--------------|--------|--------------|-------------------|------|
|                                |                       |                     |    | Min          | Typ    | Max          |                   |      |
| Contrast Ratio                 |                       | CR                  |    | 1000         | 1300   |              |                   | 1    |
| Surface Luminance, white       |                       | L <sub>WH</sub>     |    | 400          | 500    |              | cd/m <sup>2</sup> | 2    |
| Luminance Variation            |                       | δ <sub>WHITE</sub>  | 5P |              |        | 1.3          |                   | 3    |
| Response Time                  | Gray-to-Gray          | G to G              |    | -            | 10     | 15           | ms                | 4    |
|                                | Uniformity            | δ <sub>G TO G</sub> |    | -            | -      | 1            | ms                | 5    |
| Color Coordinates<br>[CIE1931] | RED                   | Rx                  |    | Typ<br>-0.03 | 0.639  | Typ<br>+0.03 |                   |      |
|                                |                       | Ry                  |    |              | 0.334  |              |                   |      |
|                                | GREEN                 | Gx                  |    |              | 0.290  |              |                   |      |
|                                |                       | Gy                  |    |              | 0.606  |              |                   |      |
|                                | BLUE                  | Bx                  |    |              | 0.146  |              |                   |      |
|                                |                       | By                  |    |              | 0.058  |              |                   |      |
|                                | WHITE                 | Wx                  |    |              | 0.279  |              |                   |      |
|                                |                       | Wy                  |    |              | 0.292  |              |                   |      |
| Color Temperature              |                       |                     |    |              | 10,000 |              | K                 |      |
| Color Gamut                    |                       |                     |    |              | 72     |              | %                 |      |
| Viewing Angle (CR>10)          |                       |                     |    |              |        |              |                   |      |
|                                | x axis, right(φ=0°)   | θ <sub>r</sub>      |    | 89           | -      | -            | degree            | 6    |
|                                | x axis, left (φ=180°) | θ <sub>l</sub>      |    | 89           | -      | -            |                   |      |
|                                | y axis, up (φ=90°)    | θ <sub>u</sub>      |    | 89           | -      | -            |                   |      |
|                                | y axis, down (φ=270°) | θ <sub>d</sub>      |    | 89           | -      | -            |                   |      |
| Gray Scale                     |                       |                     |    | -            | -      | -            |                   | 7    |

## Product Specification

Note : 1. Contrast Ratio(CR) is defined mathematically as :

CR(Contrast Ratio) = Maximum CR<sub>n</sub> (n=1, 2, 3, 4, 5)

$$CR_n = \frac{\text{Surface Luminance at position n with all white pixels}}{\text{Surface Luminance at position n with all black pixels}}$$

n = the Position number(1, 2, 3, 4, 5). For more information,

2. Surface luminance are determined after the unit has been 'ON' and 1 Hour after lighting the backlight in a dark environment at  $25 \pm 2^\circ\text{C}$ . Surface luminance is the luminance value at center 1-point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see the FIG. 2.

3. The variation in surface luminance,  $\delta$  WHITE is defined as :

$$\delta \text{ WHITE}(5P) = \text{Maximum}(L_{on1}, L_{on2}, L_{on3}, L_{on4}, L_{on5}) / \text{Minimum}(L_{on1}, L_{on2}, L_{on3}, L_{on4}, L_{on5})$$

Where  $L_{on1}$  to  $L_{on5}$  are the luminance with all pixels displaying white at 5 locations .

For more information, see the FIG. 2.

4. Response time is the time required for the display to transit from G(N) to G(M) (Rise Time,  $Tr_R$ ) and from G(M) to G(N) (Decay Time,  $Tr_D$ ). For additional information see the FIG. 3. (N<M)

※ G to G Spec stands for average value of all measured points.

Photo Detector : RD-80S / Field :  $2^\circ$

5. Gray to Gray Response time uniformity is Reference data. Please see **Appendix V**.

6. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD module surface. For more information, see the FIG. 4.

7. Gray scale specification

Gamma Value is approximately 2.2. For more information, see the Table 11.

**Table 11. GRAY SCALE SPECIFICATION**

| Gray Level | Luminance [%] (Typ) |
|------------|---------------------|
| L0         | 0.07                |
| L15        | 0.27                |
| L31        | 1.04                |
| L47        | 2.49                |
| L63        | 4.68                |
| L79        | 7.66                |
| L95        | 11.5                |
| L111       | 16.1                |
| L127       | 21.6                |
| L143       | 28.1                |
| L159       | 35.4                |
| L175       | 43.7                |
| L191       | 53.0                |
| L207       | 63.2                |
| L223       | 74.5                |
| L239       | 86.7                |
| L255       | 100                 |

## Product Specification

Measuring point for surface luminance & luminance variation




FIG. 2 5 Points for Luminance Measure

Response time is defined as the following figure and shall be measured by switching the input signal for "Gray(N)" and "Gray(M)".




FIG. 3 Response Time

## Product Specification

Dimension of viewing angle range




FIG. 4 Viewing Angle

## Product Specification

## 5. Mechanical Characteristics

Table 12 provides general mechanical characteristics.

**Table 12. MECHANICAL CHARACTERISTICS**

| Item                | Value                          |            |
|---------------------|--------------------------------|------------|
| Outline Dimension   | Horizontal                     | 1096.0 mm  |
|                     | Vertical                       | 640.0 mm   |
|                     | Depth                          | 53.0 mm    |
| Bezel Area          | Horizontal                     | 1049.0 mm  |
|                     | Vertical                       | 593.0 mm   |
| Active Display Area | Horizontal                     | 1039.68 mm |
|                     | Vertical                       | 584.82 mm  |
| Weight              | 12.5 Kg (Typ.) , 13.0Kg (Max.) |            |


Note : Please refer to a mechanical drawing in terms of tolerance at the next page.

**[ FRONT VIEW ]**



## Product Specification

## [ REAR VIEW ]



## Product Specification

## 6. Reliability

**Table 13. ENVIRONMENT TEST CONDITION**

| No. | Test Item                                    | Condition  |
|-----|--|--|
| 1   | High temperature storage test                | Ta= 60°C 240h  |
| 2   | Low temperature storage test                 | Ta= -20°C 240h   |
| 3   | High temperature operation test              | Ta= 50°C 50%RH 240h  |
| 4   | Low temperature operation test               | Ta= 0°C 240h   |
| 5   | Vibration test<br>(non-operating)            | Wave form : random<br>Vibration level : 1.0Grms<br>Bandwidth : 10-300Hz<br>Duration : X,Y,Z, 30 min<br>Each direction per 10 min |
| 6   | Shock test<br>(non-operating)                | Shock level : 50Grms<br>Waveform : half sine wave, 11ms<br>Direction : $\pm X$ , $\pm Y$ , $\pm Z$<br>One time each direction    |
| 7   | Humidity condition Operation                 | Ta= 40 °C ,90%RH   |
| 8   | Altitude     operating<br>storage / shipment | 0 - 15,000 ft<br>0 - 40,000 ft   |

Note : Before and after Reliability test, LCM should be operated with normal function.



## **7. International Standards**

### **7-1. Safety**

- a) UL 60065, Seventh Edition, Underwriters Laboratories Inc.  
Audio, Video and Similar Electronic Apparatus - Safety Requirements.
- b) CAN/CSA C22.2 No.60065:03, Canadian Standards Association.  
Audio, Video and Similar Electronic Apparatus - Safety Requirements.
- c) EN 60065:2002 + A11:2008, European Committee for Electrotechnical Standardization (CENELEC).  
Audio, Video and Similar Electronic Apparatus - Safety Requirements.
- d) IEC 60065:2005 + A1:2005, The International Electrotechnical Commission (IEC).  
Audio, Video and Similar Electronic Apparatus - Safety Requirements.

### **7-2. EMC**

- a) ANSI C63.4 "American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz."  
American National Standards Institute (ANSI), 2003.
- b) CISPR 22 "Information technology equipment – Radio disturbance characteristics – Limit and methods of measurement." International Special Committee on Radio Interference (CISPR), 2005.
- c) CISPR 13 "Sound and television broadcast receivers and associated equipment – Radio disturbance characteristics – Limits and method of measurement." International Special Committee on Radio Interference (CISPR), 2006.

### **7-3. Environment**

- a) RoHS, Directive 2002/95/EC of the European Parliament and of the council of 27 January 2003

## Product Specification

**8. Packing****8-1. Information of LCM Label**

a) Lot Mark

|   |   |   |   |   |   |   |   |   |   |   |   |   |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
|---|---|---|---|---|---|---|---|---|---|---|---|---|

A,B,C : SIZE(INCH)  
E : MONTH

D : YEAR  
F ~ M : SERIAL NO.

Note

## 1. YEAR

|      |      |      |      |      |      |      |      |      |      |      |
|------|------|------|------|------|------|------|------|------|------|------|
| Year | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 |
| Mark | 1    | 2    | 3    | 4    | 5    | 6    | 7    | 8    | 9    | 0    |

## 2. MONTH

|       |     |     |     |     |     |     |     |     |     |     |     |     |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
| Mark  | 1   | 2   | 4   | 4   | 5   | 6   | 7   | 8   | 9   | A   | B   | C   |

b) Location of Lot Mark

Serial NO. is printed on the label. The label is attached to the backside of the LCD module.  
This is subject to change without prior notice.

**8-2. Packing Form**

a) Package quantity in one Pallet : 12 pcs

b) Pallet Size : 1300 mm X 1140 mm X 117.5 mm.

## Product Specification

## 9. Precautions

Please pay attention to the followings when you use this TFT LCD module.

### 9-1. Mounting Precautions

- (1) You must mount a module using specified mounting holes (Details refer to the drawings).
- (2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- (3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to resist external force.
- (4) You should adopt radiation structure to satisfy the temperature specification.
- (5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- (6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth. (Some cosmetics are detrimental to the polarizer.)
- (7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzine. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
- (8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (9) Do not open the case because inside circuits do not have sufficient strength.

### 9-2. Operating Precautions

- (1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :  
 $V = \pm 200\text{mV}$  (Over and under shoot voltage)
- (2) Response time depends on the temperature. (In lower temperature, it becomes longer.)
- (3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)  
 And in lower temperature, response time (required time that brightness is stable after turned on) becomes longer
- (4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
- (6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.
- (7) Please do not give any mechanical and/or acoustical impact to LCM. Otherwise, LCM can't be operated its full characteristics perfectly.
- (8) A screw which is fastened up the steels should be a machine screw.  
 (if not, it can cause conductive particles and deal LCM a fatal blow)
- (9) Please do not set LCD on its edge.
- (10) The conductive material and signal cables are kept away from transformers to prevent abnormal display, sound noise and temperature rising.
- (11) Partial darkness may happen during 3~5 minutes when LCM is operated initially in condition that luminance is under 40% at low temperature (under 5℃). This phenomenon which disappears naturally after 3~5 minutes is not a problem about reliability but LCD characteristic.

## Product Specification

- (12) Partial darkness may happen under the long-term operation of any dimming without power on/off. This phenomenon which disappears naturally after 5 minutes is not a problem about reliability but LCD characteristics.

### 9-3. Electrostatic Discharge Control

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

### 9-4. Precautions for Strong Light Exposure

Strong light exposure causes degradation of polarizer and color filter.

### 9-5. Storage

When storing modules as spares for a long time, the following precautions are necessary.

- (1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
- (2) The polarizer surface should not come in contact with any other object.  
It is recommended that they be stored in the container in which they were shipped.


### 9-6. Handling Precautions for Protection Film

- (1) The protection film is attached to the bezel with a small masking tape.  
When the protection film is peeled off, static electricity is generated between the film and polarizer. This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
- (2) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the bezel after the protection film is peeled off.
- (3) You can remove the glue easily. When the glue remains on the bezel surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

## Product Specification

## # APPENDIX-I


## ■ LD470WN-SCA1 – Pallet Ass'y




| NO. | DESCRIPTION    | MATERIAL                  |
|-----|----------------|---------------------------|
| 1   | LCD Module     |                           |
| 2   | BAG            | 47INCH                    |
| 3   | TAPE           | MASKING 20MMX50M          |
| 4   | PALLET         | Plywood 1300X1140X117.5mm |
| 5   | PACKING,BOTTOM | EPS                       |
| 6   | PACKING, TOP   | EPS                       |
| 7   | ANGLE,POST     | PAPER                     |
| 8   | ANGLE,PACKING  | PAPER                     |
| 9   | ANGLE.COVER    | PAPER                     |
| 10  | BAND,CLIP      | STEEL or PP               |
| 11  | BAND           | PP                        |
| 12  | LABEL          | YUPO 80G 100X70           |

## # APPENDIX- II-1

## ■ LD470WUN-SCA1-LCM Label




## ■ Serial No. (See CAS 26 page for more information)




## # APPENDIX- II-2

## ■ LD470WUN-SCA1-Pallet Label



## # APPENDIX- III-1

■ Required signal assignment for Flat Link (Thine : THC63LVD103) Transmitter(Pin7="L")



Note: 1. The LCD module uses a 100 Ohm[Ω] resistor between positive and negative lines of each receiver input.


2. Refer to LVDS Transmitter Data Sheet for detail descriptions. (THC63LVD103 or Compatible)

3. '9' means MSB and '0' means LSB at R,G,B pixel data.



## # APPENDIX- III-1

■ Required signal assignment for Flat Link (Thine : THC63LVD103) Transmitter(Pin7="H")



Note :1. The LCD module uses a 100 Ohm[Ω] resistor between positive and negative lines of each receiver input.


2. Refer to LVDS Transmitter Data Sheet for detail descriptions. (THC63LVD103 or Compatible)

3. '9' means MSB and '0' means LSB at R,G,B pixel data.


## # APPENDIX- III-2

## ■ LVDS Data-Mapping Information (10 Bit )

## 1) LVDS Select : “H” Data-Mapping (JEIDA format)




## 2) LVDS Select : “L” Data-Mapping (VESA format)




## # APPENDIX- III-2

## ■ LVDS Data-Mapping Information (8 Bit )

## 1) LVDS Select : "H" Data-Mapping (JEIDA format)





## 2) LVDS Select : "L" Data-Mapping (VESA format)



## # APPENDIX- III-3

## ■ Option Pin Circuit Block Diagram


1) Circuit Block Diagram of **LVDS Format** Selection pin2) Circuit Block Diagram of **OPC Enable** Selection pin

## Product Specification


## # APPENDIX- III-4

## ■ EXTVBR-B &amp; OPC Design Guide

- 1) When OPC Enable is "L", OPC Output = System Dimming.
- 2) OPC Output( PWM Signal) is synchronized with V-Sync Freq. of System in T-Con Board.
- 3) Regardless of OPC, System should always give dimming Signal (EXTVBR-B) to T-con.
- 4) PWM Specification ( VCC = 3.3V ) @ OPC
  - a) PWM High Voltage Range : 2.5 V ~ 3.6 V
  - b) PWM Low Voltage Range : 0.0 V ~ 0.8 V



|                 |  |
|-----------------|--|
| Input Frequency | MAX 1Khz<br>(Recommendation: 50~300Hz) |
| Rising Time     | MAX 10.0 $\mu$ s                       |
| Falling Time    | MAX 10.0 $\mu$ s                       |




## # APPENDIX- IV-1

■ Inverter 14<sup>th</sup> Pin (**Status**) Design Guide

## 1) Function of Status pin

- Purpose : Preventing of backlight off by restarting the inverter technically
- How to : When inverter is abnormal operation, TV system inputs the Von signal in the inverter once more to turn on the lamp safely
- Attention : Restart system's Von signal when status pin is high for some time (min:1sec , max:4sec).  
(The turn on time of lamp can be late such as the low temperature or the storage time)

## 2) Status operation modes in TV set



## 3) Inverter pin map

| Pin No | Symbol   | Description                                 | Inv.         |
|--------|----------|---|--------------|
| 11     | NC       | No Connection                               | NC           |
| 12     | VON/OFF  | 0.0V ~ 5.0V                                 | On/Off       |
| 13     | EXTVBR-B | Burst Dimming Control PWM signal input      | External PWM |
| 14     | Status   | Normal : Under 0.7V / Abnormal : Upper 3.0V | status       |