

Product Specification

SPECIFICATION FOR APPROVAL

() Preliminary Specification

(◆) Final Specification

| | |
|-------|--------------------|
| Title | 16.4" WHD+ TFT LCD |
|-------|--------------------|





| | |
|----------|------|
| Customer | SONY |
| MODEL | |

| | |
|----------|----------------------|
| SUPPLIER | LG Display Co., Ltd. |
| *MODEL | LP164WD1 |
| Suffix | TLA1 |

*When you obtain standard approval,
please use the above model name without suffix

| APPROVED BY | SIGNATURE |
|-------------|-----------|
| / | |
| / | |
| / | |

Please return 1 copy for your confirmation with your signature and comments.

| APPROVED BY | SIGNATURE |
|------------------------|---|
| K. S. Kwon / S.Manager |  '08.10.17 |
| REVIEWED BY | |
| C. I. Kim / Manager |  '08.10.17 |
| PREPARED BY | |
| J. W. Kim / Engineer |  '08.10.17 |
| B. D. Jun / Engineer |  '08.10.17 |

Products Engineering Dept.
LG Display Co., Ltd

Contents

| No | ITEM | Page |
|-----|-----------------------------------|------|
| | COVER | 1 |
| | CONTENTS | 2 |
| | RECORD OF REVISIONS | 3 |
| 1 | GENERAL DESCRIPTION | 4 |
| 2 | ABSOLUTE MAXIMUM RATINGS | 5 |
| 3 | ELECTRICAL SPECIFICATIONS | |
| 3-1 | ELECTRICAL CHARACTERISTICS | 6 |
| 3-2 | INTERFACE CONNECTIONS | 8 |
| 3-3 | LVDS SIGNAL TIMING SPECIFICATIONS | 9 |
| 3-4 | SIGNAL TIMING SPECIFICATIONS | 11 |
| 3-5 | SIGNAL TIMING WAVEFORMS | 11 |
| 3-6 | COLOR INPUT DATA REFERENCE | 12 |
| 3-7 | POWER SEQUENCE | 13 |
| 4 | OPTICAL SPECIFICATIONS | 14 |
| 5 | MECHANICAL CHARACTERISTICS | 18 |
| 6 | RELIABILITY | 25 |
| 7 | INTERNATIONAL STANDARDS | |
| 7-1 | SAFETY | 26 |
| 7-2 | EMC | 26 |
| 8 | PACKING | |
| 8-1 | Packing Ass'y | 27 |
| 8-2 | Pallet Ass'y | 28 |
| 8-3 | DESIGNATION OF LOT MARK | 29 |
| 9 | PRECAUTIONS | 30 |


3 / 31

1. General Description

The LP164WD1 is a Color Active Matrix Liquid Crystal Display with an integral Cold Cathode Fluorescent Lamp (CCFL) backlight system. The matrix employs a-Si Thin Film Transistor as the active element. It is a transmissive type display operating in the normally white mode. This TFT-LCD has 16.4 inches diagonally measured active display area with HD+ resolution(900 vertical by 1600 horizontal pixel array). Each pixel is divided into Red, Green and Blue sub-pixels or dots which are arranged in vertical stripes. Gray scale or the brightness of the sub-pixel color is determined with a 6-bit gray scale signal for each dot, thus, presenting a palette of more than 262,144 colors.

The LP164WD1 has been designed to apply the interface method that enables low power, high speed, low EMI.

The LP164WD1 is intended to support applications where thin thickness, low power are critical factors and graphic displays are important. In combination with the vertical arrangement of the sub-pixels, the LP164WD1 characteristics provide an excellent flat display for office automation products such as Notebook PC.



General Features

| | |
|------------------------|--|
| Active Screen Size | 16.4 inches diagonal |
| Outline Dimension | 375.0(H, typ) × 219.1(V, typ) × 6.5(D,max) [mm] |
| Pixel Pitch | 0.2265mm × 0.2265 mm |
| Pixel Format | 1600 horiz. By 900 vert. Pixels RGB strip arrangement |
| Color Depth | 6-bit, 262,144 colors |
| Luminance, White | 200 cd/m ² (Typ.5 point) |
| Power Consumption | Total 6.3 Watt(Typ.) @ LCM circuit 1.5 Watt(Typ.), B/L input 4.8 Watt(Typ.) |
| Weight | 625g (Max.) |
| Display Operating Mode | Transmissive mode, normally white |
| Surface Treatment | Hard Coating(3H), Surface Reflection rate(<5%), Glare treatment of the front polarizer |
| RoHS Comply | Yes |

2. Absolute Maximum Ratings


The following are maximum values which, if exceeded, may cause faulty operation or damage to the unit.

Table 1. ABSOLUTE MAXIMUM RATINGS

| Parameter | Symbol | Values | | Units | Notes |
|----------------------------|--------|--------|-----|-------|-------|
| | | Min | Max | | |
| Operating Temperature | TOP | -0.3 | 4.0 | ° C | 1 |
| Storage Temperature | HST | -20 | 60 | ° C | 1 |
| Operating Ambient Humidity | HOP | 10 | 90 | %RH | 1 |
| Storage Humidity | HST | 10 | 90 | %RH | 1 |

Note : 1. Temperature and relative humidity range are shown in the figure below.

Wet bulb temperature should be 39° C Max, and no condensation of water.



Note : 2. Not showing abnormal scanner operation when turning on LCM after 30minutes of storage at -10°C.

3. Electrical Specifications

3-1. Electrical Characteristics


The LP164WD1 requires two power inputs. One is employed to power the LCD electronics and to drive the TFT array and liquid crystal. The second input which powers the CCFL, is typically generated by an inverter. The inverter is an external unit to the LCD.

Table 2. ELECTRICAL CHARACTERISTICS

| Parameter | Symbol | Values | | | Unit | Notes |
|--|-----------------|------------|------------|------------|-------------------|-------|
| | | Min | Typ | Max | | |
| MODULE : | | | | | | |
| Power Supply Input Voltage | VCC | 3.0 | 3.3 | 3.6 | V _{DC} | |
| Power Supply Input Current | I _{CC} | - | 455 | 515 | mA | 1 |
| Power Consumption | Pc | - | 1.5 | 1.7 | Watt | 1 |
| Differential Impedance | Zm | 90 | 100 | 110 | Ohm | 2 |
| LAMP : | | | | | | |
| Operating Voltage | V _{BL} | 700(7.0mA) | 745(6.0mA) | 970(2.0mA) | V _{RMS} | |
| Operating Current | I _{BL} | 2.0 | 6.0 | 7.0 | mA _{RMS} | 3 |
| Power Consumption | P _{BL} | - | 4.5 | 4.9 | | |
| Operating Frequency | f _{BL} | 45 | 60 | 80 | kHz | |
| Discharge Stabilization Time | Ts | - | - | 3 | Min | 4 |
| Life Time | | 15,000 | - | - | Hrs | 5 |
| Established Starting Voltage at 25℃ at 0 ℃ | Vs | | | 1200 | V _{RMS} | |
| | | | | 1440 | V _{RMS} | |

Note)

1. The specified current and power consumption are under the Vcc = 3.3V , 25°C, fv = 60Hz condition whereas Mosaic pattern is displayed and fv is the frame frequency.




2. This impedance value is needed to proper display and measured form LVDS Tx to the mating connector.
3. The inrush current is measured under a maximum or minimum Vcc in black pattern.
4. The typical operating current is for the typical surface luminance (L_{WH}) in optical characteristics.
5. Define the brightness of the lamp after being lighted for 5 minutes as 100%, Ts is the time required for the brightness of the center of the lamp to be not less than 95%.
6. The life time is determined as the time at which brightness of lamp is 50% compare to that of initial value at the typical lamp current.

Product Specification

Note)

6. The output of the inverter must have symmetrical(negative and positive) voltage waveform and symmetrical current waveform.(Asymmetrical ratio is less than 10%) Please do not use the inverter which has asymmetrical voltage and asymmetrical current and spike wave.
 Lamp frequency may produce interface with horizontal synchronous frequency and as a result this may cause beat on the display. Therefore lamp frequency shall be as away possible from the horizontal synchronous frequency and from its harmonics in order to prevent interference.
 7. It is defined the brightness of the lamp after being lighted for 5 minutes as 100%.
 T_s is the time required for the brightness of the center of the lamp to be not less than 95%.
 8. The lamp power consumption shown above does not include loss of external inverter.
 The applied lamp current is a typical one.
 9. Requirements for a system inverter design, which is intended to have a better display performance, a better power efficiency and a more reliable lamp, are following.
 It shall help increase the lamp lifetime and reduce leakage current.
 - a. The asymmetry rate of the inverter waveform should be less than 10%.
 - b. The distortion rate of the waveform should be within $\sqrt{2} \pm 10\%$.
- * Inverter output waveform had better be more similar to ideal sine wave.



* Asymmetry rate:

$$|I_p - I_{-p}| / I_{rms} * 100\%$$

* Distortion rate




$$I_p \text{ (or } I_{-p}) / I_{rms}$$

10. Inverter open voltage must be more than lamp voltage for more than 1 second for start-up.
 Otherwise, the lamps may not be turned on.

※ Do not attach a conducting tape to lamp connecting wire.

If the lamp wire attach to a conducting tape, TFT-LCD Module has a low luminance and the inverter has abnormal action. Because leakage current is occurred between lamp wire and conducting tape.

Ex of current wave)



Normal current wave - Standard

Abnormal current wave - Bad

Abnormal current wave - Bad

Abnormal current wave - Bad

3-2. Interface Connections

This LCD employs two interface connections, a 30 pin connector is used for the module electronics interface and the other connector is used for the integral backlight system.

The electronics interface connector is a model FI-XB30SRL-HF11 manufactured by JAE.

Table 3. MODULE CONNECTOR PIN CONFIGURATION (CN1)

| Pin | Symbol | Description | Notes |
|-----|-------------------------|--|---|
| 1 | GND | Ground | <p>1, Interface chips 1.1 LCD : SW, SW0617 (LCD Controller) including LVDS Receiver 1.2 System : THC63LVDF823A or equivalent * Pin to Pin compatible with LVDS</p> <p>2. Connector 2.1 LCD :FI-XB30SRL-HF11 ,JAE or its compatibles 2.2 Mating : FI-X30M or equivalent. 2.3 Connector pin arrangement</p>  <p>[LCD Module Rear View]</p> |
| 2 | VCC | Power Supply, 3.3V Typ. | |
| 3 | VCC | Power Supply, 3.3V Typ. | |
| 4 | V EEDID | DDC 3.3V power | |
| 5 | NC | No Connection | |
| 6 | Clk EEDID | DDC Clock | |
| 7 | DATA EEDID | DDC Data | |
| 8 | Odd_R _{IN} 0- | Negative LVDS differential data input | |
| 9 | Odd_R _{IN} 0+ | Positive LVDS differential data input | |
| 10 | GND | Ground | |
| 11 | Odd_R _{IN} 1- | Negative LVDS differential data input | |
| 12 | Odd_R _{IN} 1+ | Positive LVDS differential data input | |
| 13 | GND | Ground | |
| 14 | Odd_R _{IN} 2- | Negative LVDS differential data input | |
| 15 | Odd_R _{IN} 2+ | Positive LVDS differential data input | |
| 16 | GND | Ground | |
| 17 | Odd_CLKIN- | Negative LVDS differential clock input | |
| 18 | Odd_CLKIN+ | Positive LVDS differential clock input | |
| 19 | GND | Ground | |
| 20 | Even_R _{IN} 0- | Negative LVDS differential data input | |
| 21 | Even_R _{IN} 0+ | Positive LVDS differential data input | |
| 22 | GND | Ground | |
| 23 | Even_R _{IN} 1- | Negative LVDS differential data input | |
| 24 | Even_R _{IN} 1+ | Positive LVDS differential data input | |
| 25 | GND | Ground | |
| 26 | Even_R _{IN} 2- | Negative LVDS differential data input | |
| 27 | Even_R _{IN} 2+ | Positive LVDS differential data input | |
| 28 | GND | Ground | |
| 29 | Even_CLKIN- | Negative LVDS differential clock input | |
| 30 | Even_CLKIN+ | Positive LVDS differential clock input | |

The backlight interface connector is a model BL-HSR-02VS-1, manufactured by JST or Compatible.

The mating connector part number is AMP1674817-2 or equivalent.





Table 4. BACKLIGHT CONNECTOR PIN CONFIGURATION (J3)

| Pin | Symbol | Description | Notes |
|-----|--------|---|-------|
| 1 | HV | Power supply for lamp (High voltage side) | 1 |
| 2 | LV | Power supply for lamp (Low voltage side) | 1 |

Notes : 1. The high voltage side terminal is colored Blue and the low voltage side terminal is Black.


3-3. LVDS Signal Timing Specifications

3-3-1. DC Specification




| Description | Symbol | Min | Max | Unit | Notes |
|---------------------------|------------|-----|-----|------|-------|
| LVDS Differential Voltage | $ V_{ID} $ | 100 | 600 | mV | - |
| LVDS Common mode Voltage | V_{CM} | 0.6 | 1.8 | V | - |
| LVDS Input Voltage Range | V_{IN} | 0.3 | 2.1 | V | - |

3-3-2. AC Specification




| Description | Symbol | Min | Max | Unit | Notes |
|--|----------------|-------|---------|-----------|------------------------------|
| LVDS Clock to Data Skew Margin | t_{SKEW} | - 400 | + 400 | ps | $85MHz > F_{clk} \geq 65MHz$ |
| | t_{SKEW} | - 600 | + 600 | ps | $65MHz > F_{clk} \geq 25MHz$ |
| LVDS Clock to Clock Skew Margin (Even to Odd) | t_{SKEW_EO} | - 1/7 | + 1/7 | T_{clk} | - |
| Maximum deviation of input clock frequency during SSC | F_{DEV} | - | ± 3 | % | - |
| Maximum modulation frequency of input clock during SSC | F_{MOD} | - | 200 | KHz | - |

Product Specification




< Clock skew margin between channel >



< Spread Spectrum >

3-3-3. Data Format

1) LVDS 2 Port



< LVDS Data Format >

3-4. Signal Timing Specifications


This is the signal timing required at the input of the User connector. All of the interface signal timing should be satisfied with the following specifications and specifications of LVDS Tx/Rx for its proper operation.

Table 6. TIMING TABLE

| ITEM | Symbol | | Min | Typ | Max | Unit | Note |
|-------------|------------------------|-----------|--------|--------|--------|------|------------------------------|
| DCLK | Frequency | f_{CLK} | 47.375 | 48.875 | 50.375 | MHz | 1port : $f_{CLK} * 2$ |
| Hsync | Period | t_{HP} | 862 | 880 | 898 | tCLK | 1port : Hsync * 2 |
| | Width | t_{WH} | 12 | 16 | 20 | | |
| | Width-Active | t_{WHA} | 800 | 800 | 800 | | |
| Vsync | Period | t_{VP} | 916 | 926 | 935 | tVP | |
| | Width | t_{WV} | 3 | 5 | 8 | | |
| | Width-Active | t_{WVA} | 900 | 900 | 900 | | |
| Data Enable | Horizontal back porch | t_{HBP} | 32 | 40 | 48 | tCLK | 1port : Horizontal porch * 2 |
| | Horizontal front porch | t_{HFP} | 18 | 24 | 30 | | |
| | Vertical back porch | t_{VBP} | 11 | 18 | 22 | tHP | |
| | Vertical front porch | t_{VFP} | 2 | 3 | 5 | | |

3-5. Signal Timing Waveforms

Condition : $V_{CC} = 3.3V$



3-6. Color Input Data Reference

The brightness of each primary color (red, green and blue) is based on the 6-bit gray scale data input for the color ; the higher the binary input, the brighter the color. The table below provides a reference for color versus data input.

Table 7. COLOR DATA REFERENCE

| Color | | Input Color Data | | | | | | | | | | | | | | | | | |
|-------------|------------|------------------|----|-----|----|----|-----|-------|----|-----|----|-----|-----|------|----|-----|----|----|-----|
| | | RED | | | | | | GREEN | | | | | | BLUE | | | | | |
| | | MSB | | LSB | | | | MSB | | LSB | | | | MSB | | LSB | | | |
| | | R5 | R4 | R3 | R2 | R1 | R0 | G5 | G4 | G3 | G2 | G1 | G0 | B5 | B4 | B3 | B2 | B1 | B0 |
| Basic Color | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Blue | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Cyan | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Magenta | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Yellow | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | White | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| RED | RED (00) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | RED (01) | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | ... | | | | | | ... | | | | | | ... | | | | | | ... |
| | RED (62) | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | RED (63) | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| GREEN | GREEN (00) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | GREEN (01) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | ... | | | | | | ... | | | | | ... | | | | | | | ... |
| | GREEN (62) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | GREEN (63) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| BLUE | BLUE (00) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | BLUE (01) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
| | ... | | | | | | ... | | | | | ... | | | | | | | ... |
| | BLUE (62) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 |
| | BLUE (63) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |

3-7. Power Sequence




Table 8. POWER SEQUENCE TABLE

| Parameter | Value | | | Units |
|----------------|-------|------|------|-------|
| | Min. | Typ. | Max. | |
| T ₁ | 0 | - | 10 | (ms) |
| T ₂ | 0 | - | 50 | (ms) |
| T ₃ | 200 | - | - | (ms) |
| T ₄ | 200 | - | - | (ms) |
| T ₅ | 0 | - | 50 | (ms) |
| T ₆ | 3 | - | 10 | (ms) |
| T ₇ | 400 | - | - | (ms) |

Note)

1. Valid Data is Data to meet "3-3. LVDS Signal Timing Specifications"
2. Please avoid floating state of interface signal at invalid period.
3. When the interface signal is invalid, be sure to pull down the power supply for LCD VCC to 0V.
4. Lamp power must be turn on after power supply for LCD and interface signal are valid.

4. Optical Specification

Optical characteristics are determined after the unit has been 'ON' and stable for approximately 30 minutes in a dark environment at 25° C. The values specified are at an approximate distance 50cm from the LCD surface

at a viewing angle of Φ and Θ equal to 0° .

FIG. 1 presents additional information concerning the measurement equipment and method.

FIG. 1 Optical Characteristic Measurement Equipment and Method




Table 9. OPTICAL CHARACTERISTICS

Ta=25° C, VCC=3.3V, fv=60Hz, f_{CLK}= 48.875MHz, F_{BL}= 60KHz, I_{BL}= 6.0mA

| Parameter | Symbol | Values | | | Units | Notes |
|-----------------------------------|-------------------------|--------|-------|-------|-------------------|-------|
| | | Min | Typ | Max | | |
| Contrast Ratio | CR | 400 | 600 | - | | 1 |
| Surface Luminance, white | L _{WH} | 170 | 200 | - | cd/m ² | 2 |
| Luminance Variation | δ_{WHITE} | - | 1.4 | 1.6 | | 3 |
| Response Time | | | | | | 4 |
| (Rise time) | Tr _R | - | 5.5 | 9 | ms | |
| (Delay time) | Tr _D | - | 10.5 | 16 | ms | |
| Color Coordinates | | | | | | |
| RED | RX | 0.564 | 0.594 | 0.624 | | |
| | RY | 0.317 | 0.347 | 0.377 | | |
| GREEN | GX | 0.299 | 0.329 | 0.359 | | |
| | GY | 0.516 | 0.546 | 0.576 | | |
| BLUE | BX | 0.126 | 0.156 | 0.186 | | |
| | BY | 0.106 | 0.136 | 0.166 | | |
| WHITE | WX | 0.283 | 0.313 | 0.343 | | |
| | WY | 0.299 | 0.329 | 0.359 | | |
| Viewing Angle | | | | | | 5 |
| x axis, right($\Phi=0^\circ$) | Θ | 40 | 45 | - | degree | |
| x axis, left ($\Phi=180^\circ$) | Θ | 40 | 45 | - | degree | |
| y axis, up ($\Phi=90^\circ$) | Φ | 15 | 20 | - | degree | |
| y axis, down ($\Phi=270^\circ$) | Φ | 35 | 40 | - | degree | |
| Gray Scale | | | 2.2 | - | | 6 |

Product Specification

Note)

1. Contrast Ratio(CR) is defined mathematically as

$$\text{Contrast Ratio} = \frac{\text{Surface Luminance with all white pixels}}{\text{Surface Luminance with all black pixels}}$$

2. Surface luminance is the average of 5 point across the LCD surface 50cm from the surface with all pixels displaying white. For more information see FIG 1.

$$L_{WH} = \text{Average}(L_1, L_2, \dots L_5)$$

3. The variation in surface luminance , The panel total variation (δ_{WHITE}) is determined by measuring L_N at each test position 1 through 13 and then defined as followed numerical formula.
For more information see FIG 2.

$$\delta_{WHITE} = \frac{\text{Maximum}(L_1, L_2, \dots L_{13})}{\text{Minimum}(L_1, L_2, \dots L_{13})}$$

4. Response time is the time required for the display to transition from white to black (rise time, Tr_R) and from black to white(Decay Time, Tr_D). For additional information see FIG 3.
5. Viewing angle is the angle at which the contrast ratio is greater than 10. The angles are determined for the horizontal or x axis and the vertical or y axis with respect to the z axis which is normal to the LCD surface. For more information see FIG 4.


6. Gray scale specification

* $f_v = 60\text{Hz}$

| Gray Level | Luminance [%] (Typ) |
|------------|---------------------|
| L0 | 0.1 |
| L7 | 1.8 |
| L15 | 6.3 |
| L23 | 12.6 |
| L31 | 21.0 |
| L39 | 33.6 |
| L47 | 51.8 |
| L55 | 74.6 |
| L63 | 100 |

FIG. 2 Luminance

<measuring point for surface luminance & measuring point for luminance variation>


FIG. 3 Response Time

The response time is defined as the following figure and shall be measured by switching the input signal for “black” and “white”.





FIG. 4 Viewing angle

<Dimension of viewing angle range>




5. Mechanical Characteristics

The contents provide general mechanical characteristics for the model LP164WD1. In addition the figures in the next page are detailed mechanical drawing of the LCD.

| | | |
|---------------------|--|----------------|
| Outline Dimension | Horizontal | 375.0 ± 0.5mm |
| | Vertical | 219.1 ± 0.5mm |
| | Thickness | 6.5mm (max) |
| Bezel Area | Horizontal | 365.9 ± 0.5mm |
| | Vertical | 207.35 ± 0.5mm |
| Active Display Area | Horizontal | 362.4 mm |
| | Vertical | 203.85 mm |
| Weight | 625g (Max.) | |
| Surface Treatment | Hard Coating(3H), Glare treatment of the front polarizer | |

<FRONT VIEW>

Note) Unit:[mm], General tolerance: $\pm 0.5\text{mm}$




Note) Unit:[mm], General tolerance: $\pm 0.5\text{mm}$



Product Specification



[DETAIL DESCRIPTION OF SIDE MOUNTING SCREW]





- * Mounting Screw Length (A)
 = 2.0(Min) / 2.5(Max)
- * Mounting Screw Hole Depth (B)
 = 2.5(Min)
- * Mounting hole location : 3.70(typ.)
- * Torque : 2.0 kgf.cm(Max)
 (Measurement gauge : torque meter)

Notes : 1. Screw plated through the method of non-electrolytic nickel plating is preferred to reduce possibility that results in vertical and/or horizontal line defect due to the conductive particles from screw surface.





LGD Proposal for system cover design.(Appendix)

| | | |
|--------|--|--|
| 1 | Gap check for securing the enough gap between LCM and System cover. | |
| |  <p style="text-align: center;">LCM Reflector Side</p> | |
| Define | 1.Rear side of LCM is sensitive against external stress,and previous check about interference is highly needed. 2.In case there is something from system cover comes into the boundary above,mechanical interference may cause the FOS defects. (Eg:Ripple,White spot..) | |
| 2 | Check if antenna cable is sufficiently apart from T-CON of LCD Module. | |
| Define |  <p style="text-align: center;">NO GOOD GOOD</p> | |
| | 1.If system antenna is overlapped with T-CON,it might be cause the noise. | |

LGD Proposal for system cover design.

| | | |
|--------|--|--|
| 3 | Gap check for securing the enough gap between LCM and System hinge. | |
| |  <p>LCM Reflector Side</p> <p>Side Mount Screw Hole (4ea)</p> <p>Hinge</p> <p>GAP:Min2.0mm</p> <p>(“I” TYPE)</p> <p>(“L” TYPE)</p> <p>Lamp</p> | |
| Define | 1. At least 2.0mm of gap needs to be secured to prevent the shock related defects. 2. “L” type of hinge is recommended than “I” type under shock test. | |
| 4 | Checking the path of the System wire. | |
| |  <p>#8 #7 #6 #5 #4 #3 #2 #1</p> <p>Good Ok Bad</p> | |
| Define | 1. COF area needs to be handled with care. 2. GOOD → Wire path design to system side. OK → Wire path is located between COFs. BAD → Wire path overlapped with COF area. | |

LGD Proposal for system cover design.

| | | |
|---|---|--|
| 5 | Using a bracket on the top of LCM is not recommended. | |
| <div style="display: flex; justify-content: space-around; align-items: flex-start;"> <div style="text-align: center;">  <p>bracket</p>  <p>With bracket</p> </div> <div style="text-align: center;">  <p>Without bracket</p> </div> </div> | | |
| Define | 1.Condition without bracket is good for mechanical noise,and can minimize the light leakage from deformation of bracket. | |
| | 2.The results shows that there is no difference between the condition with or without bracket. | |
| 6 | Securing additional gap on CNT area.. | |
| |  | |
| Define | 1.CNT area is specially sensitive against external stress,and additional gap by cutting on system cover will be helpful on removing the Ripple. 2.Using a thinner CNT will be better. (eg: FPC type) | |

6. Reliability

Environment test condition

| No. | Test Item | Conditions |
|-----|---|--|
| 1 | High temperature storage test | Ta= 60° C, 240h |
| 2 | Low temperature storage test | Ta= -20° C, 240h |
| 3 | High temperature operation test | Ta= 50° C, 50%RH, 240h |
| 4 | Low temperature operation test | Ta= 0° C, 240h |
| 5 | Vibration test (non-operating) | Sine wave, 10 ~ 500 ~ 10Hz, 1.5G, 0.37oct/min 3 axis, 1hour/axis |
| 6 | Shock test (non-operating) | Half sine wave, 180G, 2ms one shock of each six faces(I.e. run 180G 2ms for all six faces) |
| 7 | Altitude operating storage / shipment | 0 ~ 10,000 feet (3,048m) 24Hr 0 ~ 40,000 feet (12,192m) 24Hr |

{ Result Evaluation Criteria }

There should be no change which might affect the practical display function when the display quality test is conducted under normal operating condition.

7. International Standards

7-1. Safety

- a) UL 60950-1:2003, First Edition, Underwriters Laboratories, Inc., Standard for Safety of Information Technology Equipment.
- b) CAN/CSA C22.2, No. 60950-1-03 1st Ed. April 1, 2003, Canadian Standards Association, Standard for Safety of Information Technology Equipment.
- c) EN 60950-1:2001, First Edition, European Committee for Electrotechnical Standardization(CENELEC) European Standard for Safety of Information Technology Equipment.


7-2. EMC

- a) ANSI C63.4 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electrical Equipment in the Range of 9kHz to 40GHz. "American National Standards Institute(ANSI), 1992
- b) C.I.S.P.R "Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment." International Special Committee on Radio Interference.
- c) EN 55022 "Limits and Methods of Measurement of Radio Interface Characteristics of Information Technology Equipment." European Committee for Electrotechnical Standardization.(CENELEC), 1998 (Including A1: 2000)

8. Packing

8-1. Packing Ass'y


- 1) Package quantity in one box : 20 pcs
- 2) Box Size : 480mm × 370mm × 299mm




| | | |
|---|-----------------|------|
| ① | LCM | |
| ② | TAPE | OPP |
| ③ | BAG | LDPE |
| ④ | PACKING, TOP | EPS |
| ⑤ | PACKING, BOTTOM | EPS |
| ⑥ | BOX | SWR4 |
| ⑦ | TAPE | OPP |
| ⑧ | LABEL | ID |

8-2. Pallet Ass'y

- 1) Box quantity in one pallet : 18 boxes
- 2) Package quantity in one pallet : 360 pcs



18 BOXES / 1 PALLET



| | | |
|---|----------------|---------|
| 6 | LABEL | ART |
| 5 | BAND, CLIP | STEEL |
| 4 | BAND, PACKING | P.P |
| 3 | ANGLE, PACKING | SW |
| 2 | PALLET | PLYWOOD |
| 1 | PACKING ASS'Y | |

8-3. Designation of Lot Mark

a) Lot Mark

| | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| A | B | C | D | E | F | G | H | I | J | K | L | M |
|---|---|---|---|---|---|---|---|---|---|---|---|---|

A,B,C : SIZE(INCH)

E : MONTH

D : YEAR

F ~ M : SERIAL NO.

Note

1. YEAR

| Year | 2001 | 2002 | 2003 | 2004 | 2005 | 2006 | 2007 | 2008 | 2009 | 2010 |
|------|------|------|------|------|------|------|------|------|------|------|
| Mark | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 0 |

2. MONTH

| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|-------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| Mark | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | A | B | C |

b) Location of Lot Mark

Serial No. is printed on the label. The label is attached to the backside of the LCD module.
This is subject to change without prior notice.

9. PRECAUTIONS

Please pay attention to the followings when you use this TFT LCD module.

9-1. MOUNTING PRECAUTIONS

- (1) You must mount a module using holes arranged in four corners or four sides.
- (2) You should consider the mounting structure so that uneven force (ex. Twisted stress) is not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- (3) Please attach the surface transparent protective plate to the surface in order to protect the polarizer. Transparent protective plate should have sufficient strength in order to resist external force.
- (4) You should adopt radiation structure to satisfy the temperature specification.
- (5) Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- (6) Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. And please do not rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth. (Some cosmetics are detrimental to the polarizer.)
- (7) When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzene. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
- (8) Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer causes deformations and color fading.
- (9) Do not open the case because inside circuits do not have sufficient strength.

9-2. OPERATING PRECAUTIONS

- (1) The spike noise causes the mis-operation of circuits. It should be lower than following voltage :
 $V = \pm 200\text{mV}$ (Over and under shoot voltage)
- (2) Response time depends on the temperature. (In lower temperature, it becomes longer.)
- (3) Brightness depends on the temperature. (In lower temperature, it becomes lower.)
And in lower temperature, response time (required time that brightness is stable after turned on) becomes longer.
- (4) Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- (5) When fixed patterns are displayed for a long time, remnant image is likely to occur.
- (6) Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimize the interference.

9-3. ELECTROSTATIC DISCHARGE CONTROL

Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

9-4. PRECAUTIONS FOR STRONG LIGHT EXPOSURE

Strong light exposure causes degradation of polarizer and color filter.

9-5. STORAGE

When storing modules as spares for a long time, the following precautions are necessary.

- (1) Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5° C and 35° C at normal humidity.
- (2) The polarizer surface should not come in contact with any other object.
It is recommended that they be stored in the container in which they were shipped.

9-6. HANDLING PRECAUTIONS FOR PROTECTION FILM

- (1) When the protection film is peeled off, static electricity is generated between the film and polarizer.
This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
- (2) The protection film is attached to the polarizer with a small amount of glue. If some stress is applied to rub the protection film against the polarizer during the time you peel off the film, the glue is apt to remain on the polarizer.
Please carefully peel off the protection film without rubbing it against the polarizer.
- (3) When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the polarizer after the protection film is peeled off.
- (4) You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.