< ATTACHMENT 2 >

Main Specifications of the New 10.4-Inch LCD Module

Part number:	NL8060BC26-30C
Resolution:	800(H) × 600(V) pixels
Display area:	211.2 (H) × 158.4 (V) mm Diagonal screen size of 10.4 inches (26cm)
Drive system:	Amorphous-silicon TFT active-matrix
Display color:	16.77M colors / 262K colors
Pixel arrangement:	RGB vertical stripe
Pixel pitch:	0.264 (H) × 0.264 (V) mm
Luminance:	550cd/m^2 (typ.)
Contrast ratio:	900:1 (typ.)
Viewing angle:	Vertical : Up 80 degrees, down 80 degrees Horizontal : Left 80 degrees, right 80 degrees (contrast ratio at over 10:1)
Response time:	18ms (typ.) (TON + TOFF: from 10% to 90%)
Interface:	LVDS (RGB 8 bits each / 6 bits each)
Power supply voltage:	3.3V
Power consumption:	6.6W (typ.) (Power dissipation of the inverter is not included.)
Operating temperature:	-20 degrees C to +70 degrees C
Storage temperature:	-30 degrees C to +80 degrees C
Polarizer surface:	Clear + Antireflection
Module size:	243.0 (typ.) × 185.1 (typ.) × 11.0 (max.) mm
Weight:	475g (typ.)
Backlight:	One side, 2 CCFLs
Recommended inverter:	104PW201

Note: *The press release and other information in this file may be out of date on observation.*

***